

# K-SVKM NW 7,8 SCHL TUE H

Quick disconnect couplings DN 7.8 - for extremely high flow rates, with hose stem

**HANSA FLEX**

## Caratteristiche

Pressione d'esercizio	0 - 35 bar
Portata aria	2.100 l/min (at $\Delta p = 0.5$ bar)
Temperatura del fluido	-20 °C to +40 °C
Elemento filettato	Nickel-plated brass
Corpo valvola	Steel, QPQ treated
Bussola di sblocco	Extremely robust, ergonomic plastic
Valvola, sede	Brass
Mezzi	Only for clean compressed air
Guarnizioni di tenuta	NBR
Molla, anello elastico, sfere	stain less steel



## Nota

Altri dati su richiesta.

## Descrizione

One-hand quick disconnect couplings, one side sealing, that combine high flow rates (approx. twice as high as the popular DN 7.2 standard coupling) with minimal coupling forces. Suitable for all applications with an above-average air requirement!

## Articolo

Denominazione	Attacco	Lunghezza (mm)	SW (mm)
K- 07 35 08 53	Stem, I.D. 6	80,0	19
K- 07 35 12 41	Stem, I.D. 8	80,0	19
K- 07 35 08 54	Stem, I.D. 9	80,0	19
K- 07 35 12 42	Stem, I.D. 10	80,0	19
K- 07 35 08 55	Stem, I.D. 13	80,0	19

## Elementi supplementari

K-NIPP KUPPL NW7 SCHL MS NI K	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose with swivel nut and kink protector spring
K-NIPPEL KUPPL NW7 AG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, male
K-NIPPEL KUPPL NW7 IG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, female
K-NIPPEL KUPPL NW7 SCHL MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose
K-TUE 7,2 7,8 MS NI	Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass