


K-SVKM NW 7,2 IG MS-NI CL

Quick-lock couplings DN 7.2, nickel-plated brass, female

HANSA FLEX

Caratteristiche

| | |
|---------------------------------------|---|
| Pressione d'esercizio | 0 - 35 bar, maximum static working pressure (non-pulsating) |
| Temperatura del fluido | -20 °C to +100 °C |
| Alloggiamento, bussola, corpo valvola | Nickel-plated brass |
| Molla, anello elastico, perni | Stainless steel |
| Materiale di tenuta | NBR |



Nota

Altri dati su richiesta.

Descrizione

Universal, one-hand quick disconnect couplings, one side sealing, at an unbeatably low price. Compatible with CEJN 320, Rectus 25/26 and JWL 520/530. The closed sleeve protects the coupling from dirt. In combination with steel plugs, this coupling can also be used for pneumatic tools thanks to its hardened locking pins.

Articolo

| Denominazione | Attacco | Lunghezza (mm) | SW (mm) |
|----------------|--------------|-------------------|------------|
| K- 07 35 07 71 | G 1/4 female | 40,5 | 21 |
| K- 07 35 07 72 | G 3/8 female | 40,5 | 21 |
| K- 07 35 07 73 | G 1/2 female | 42,5 | 24 |