

K-PRAEZI DRUCKREGL OHNE EIGENLUF

Precision pressure regulators without air consumption

HANSA FLEX

Caratteristiche

Pressione d'ingresso	Max. 16 bar
Temperatura del fluido	max. 80 °C
Temperatura ambiente	Max. 80 °C
Mezzi	Fine-filtered (5 µm), unlubricated compressed air, neutral gases
Attacco manometro	G 1/4
Materiale di tenuta	NBR
Alloggiamento	Die-cast zinc
Cono valvola, membrana	FPM



Nota

Altri dati su richiesta.

Descrizione

Diaphragm pressure regulators with self-relieving design for applications requiring an accurate working pressure.

Articolo

Denominazione	Filetto	Intervallo di regolazione	Portata (L/min)	A (mm)	B	C (mm)	D (mm)
K- 07 25 09 39	G 1/4	0 - 1 bar	600	82,0	148,0 mm	19,5	128,5
K- 07 25 09 40	G 1/4	0.1 - 3 bar	760	82,0	148,0 mm	19,5	128,5
K- 07 25 09 41	G 1/4	0.2 - 6 bar	550	82,0	148,0 mm	19,5	128,5
K- 07 25 09 42	G 1/4	0.5 - 10 bar	400	82,0	148,0 mm	19,5	128,5

Accessori

K-HALTERBAUSATZ STANDARD Holder