

K-KOMP ZYL DOPPELW IG

Compact cylinders, double-acting (with magnet), non-cushioned, female piston rod

HANSA FLEX

Caratteristiche

Mezzi	Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.
Pressione di lavoro	Max. 10 bar
Pressione di intervento	0,6 bar (Ø 20 bis Ø 32), 0,4 bar (Ø 40 bis Ø 100)
Campo della temperatura:	-10 °C to +60 °C (Ø 20 to Ø 63) -10 °C to +80 °C (Ø 80 bis Ø 100)
Stelo del pistone	C45 steel, hard chrome-plated
Tube	Anodised aluminium jacket with T-slots
Pistone	POM (Ø 20 to Ø 63); Aluminium (Ø 80 to Ø 100)
Materiale di tenuta	NBR



Nota

Altri dati su richiesta.

Descrizione

New series acc. to ISO 21287 characterised by a very short and compact design. The standard type features a magnetic piston. Piston rod optionally with male or female thread.

Articolo

Denominazione	Ø pistone	Corsa (mm)	Attacco	Filettatura interna stelo pistone
K- 07 15 08 87	20 mm	5	M 5	M 6
K- 07 15 08 88	20 mm	10	M 5	M 6
K- 07 15 08 89	20 mm	15	M 5	M 6
K- 07 15 08 90	20 mm	20	M 5	M 6
K- 07 15 08 91	20 mm	25	M 5	M 6
K- 07 15 08 92	20 mm	30	M 5	M 6
K- 07 15 08 93	20 mm	40	M 5	M 6
K- 07 15 08 94	20 mm	50	M 5	M 6
K- 07 15 08 95	20 mm	60	M 5	M 6
K- 07 15 08 96	25 mm	5	M 5	M 6
K- 07 15 08 97	25 mm	10	M 5	M 6
K- 07 15 08 98	25 mm	15	M 5	M 6
K- 07 15 08 99	25 mm	20	M 5	M 6
K- 07 15 09 00	25 mm	25	M 5	M 6
K- 07 15 09 01	25 mm	30	M 5	M 6
K- 07 15 09 02	25 mm	40	M 5	M 6
K- 07 15 09 03	25 mm	50	M 5	M 6
K- 07 15 09 04	25 mm	60	M 5	M 6
K- 07 15 09 05	32 mm	5	G 1/8	M 8
K- 07 15 09 06	32 mm	10	G 1/8	M 8
K- 07 15 09 07	32 mm	15	G 1/8	M 8
K- 07 15 09 08	32 mm	20	G 1/8	M 8
K- 07 15 09 09	32 mm	25	G 1/8	M 8
K- 07 15 09 10	32 mm	30	G 1/8	M 8
K- 07 15 09 11	32 mm	40	G 1/8	M 8
K- 07 15 09 12	32 mm	50	G 1/8	M 8
K- 07 15 09 13	32 mm	60	G 1/8	M 8
K- 07 15 09 14	32 mm	80	G 1/8	M 8
K- 07 15 09 15	40 mm	5	G 1/8	M 8
K- 07 15 09 16	40 mm	10	G 1/8	M 8
K- 07 15 09 17	40 mm	15	G 1/8	M 8
K- 07 15 09 18	40 mm	20	G 1/8	M 8
K- 07 15 09 19	40 mm	25	G 1/8	M 8
K- 07 15 09 20	40 mm	30	G 1/8	M 8
K- 07 15 09 21	40 mm	40	G 1/8	M 8
K- 07 15 09 22	40 mm	50	G 1/8	M 8
K- 07 15 09 23	40 mm	60	G 1/8	M 8



Nonostante il più attento esame non si possono escludere eventuali errori ed omissioni, non ci assumiamo alcuna responsabilità per le indicazioni contenute.

05.06.2026

HANSA-FLEX AG

www.hansa-flex.com

1

K-KOMP ZYL DOPPELW IG

Compact cylinders, double-acting (with magnet), non-cushioned, female piston rod

HANSA FLEX

Articolo

Denominazione	Ø pistone	Corsa (mm)	Attacco	Filettatura interna stelo pistone
K- 07 15 09 24	40 mm	80	G 1/8	M 8
K- 07 15 09 25	50 mm	5	G 1/8	M 10
K- 07 15 09 26	50 mm	10	G 1/8	M 10
K- 07 15 09 27	50 mm	15	G 1/8	M 10
K- 07 15 09 28	50 mm	20	G 1/8	M 10
K- 07 15 09 29	50 mm	25	G 1/8	M 10
K- 07 15 09 30	50 mm	30	G 1/8	M 10
K- 07 15 09 31	50 mm	40	G 1/8	M 10
K- 07 15 09 32	50 mm	50	G 1/8	M 10
K- 07 15 09 33	50 mm	60	G 1/8	M 10
K- 07 15 09 34	50 mm	80	G 1/8	M 10
K- 07 15 09 35	63 mm	5	G 1/8	M 10
K- 07 15 09 36	63 mm	10	G 1/8	M 10
K- 07 15 09 37	63 mm	15	G 1/8	M 10
K- 07 15 09 38	63 mm	20	G 1/8	M 10
K- 07 15 09 39	63 mm	25	G 1/8	M 10
K- 07 15 09 40	63 mm	30	G 1/8	M 10
K- 07 15 09 41	63 mm	40	G 1/8	M 10
K- 07 15 09 42	63 mm	50	G 1/8	M 10
K- 07 15 09 43	63 mm	60	G 1/8	M 10
K- 07 15 09 44	63 mm	80	G 1/8	M 10
K- 07 15 09 45	80 mm	5	G 1/8	M 12
K- 07 15 09 46	80 mm	10	G 1/8	M 12
K- 07 15 09 47	80 mm	15	G 1/8	M 12
K- 07 15 09 48	80 mm	20	G 1/8	M 12
K- 07 15 09 49	80 mm	25	G 1/8	M 12
K- 07 15 09 50	80 mm	30	G 1/8	M 12
K- 07 15 09 51	80 mm	40	G 1/8	M 12
K- 07 15 09 52	80 mm	50	G 1/8	M 12
K- 07 15 09 53	80 mm	60	G 1/8	M 12
K- 07 15 09 54	80 mm	80	G 1/8	M 12
K- 07 15 08 77	100 mm	5	G 1/8	M 12
K- 07 15 08 78	100 mm	10	G 1/8	M 12
K- 07 15 08 79	100 mm	15	G 1/8	M 12
K- 07 15 08 80	100 mm	20	G 1/8	M 12
K- 07 15 08 81	100 mm	25	G 1/8	M 12
K- 07 15 08 82	100 mm	30	G 1/8	M 12
K- 07 15 08 83	100 mm	40	G 1/8	M 12
K- 07 15 08 84	100 mm	50	G 1/8	M 12
K- 07 15 08 85	100 mm	60	G 1/8	M 12
K- 07 15 08 86	100 mm	80	G 1/8	M 12