

K-SVKM NW 5 SCHL UEB MS BL

Quick disconnect couplings DN 5, brass with a bare metal surface, with swivel nut and kink protector spring

HANSA FLEX

Caratteristiche

Pressione d'esercizio	0 - 35 bar, maximum static working pressure (non-pulsating)
Portata aria	560 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Temperatura del fluido	-20 °C to +100 °C
Alloggiamento, bussola, corpo valvola	Brass
Molla, anello elastico, sfere	Stainless steel
Materiale di tenuta	NBR



Nota

Altri dati su richiesta.

Descrizione

One-hand quick disconnect couplings, one side sealing, compact with a large bore and only a small pressure drop. Ideal for: Pneumatic tools, pneumatic applications, medical equipment, instrumentation and control, laboratory, chemical applications, analysis, metering techniques.

Articolo

Denominazione	Attacco	Esecuzione	Lunghezza (mm)	SW (mm)
K- 07 35 06 48	Hose connection 6 x 4	Rigid	120,0	14
K- 07 35 06 49	Hose connection 8 x 6	Rigid	132,0	14
K- 07 35 06 50	Hose connection 6 x 4	Swivelling 360°	134,0	14
K- 07 35 06 51	Hose connection 8 x 6	Swivelling 360°	145,0	14