


K-WV 3/2 5/2 NAMUR LB LF

3/2- and 5/2-way spool valves with NAMUR style interface and air spring

HANSA FLEX

Caratteristiche

Mezzi	Air, neutral gases (filtered)
Pressione di lavoro	1.5 to 10 bar (552.11 and 552.12); 2.5 to 10 bar (552.21 and 552.22)
Temperatura d'esercizio	-20 °C to +50 °C
Attacco 1 - 3	G 1/4 (Port 1), G 1/4 (Port 3 and 5)
Attacco 1/3 + 5	G 1/4 (Port 1), G 1/4 (Port 3 and 5)
Collegamento elettrico	Plug connector PG 9
In dotazione	Plug connector PG 9, conversion plate, screws and seal
Potenza assorbita	3 W=5 VA~
Alloggiamento	Anodised aluminium
Valvola a cursore	Stainless steel
Materiale di tenuta	NBR



Nota

Altri dati su richiesta.

Descrizione

Pilot-operated 3/2- and 5/2-way spool valves with threaded ports and a NAMUR style interface with air purging function. By adding the conversion plate supplied with each valve, the device can be adapted to 3/2-way function.

Filter regulators are also available with bowl guard or metal bowl. Filter regulators are also available in lockable version. Please ask for more information.

Articolo

Denominazione	Tensione	Port 1	Attacco 3 + 5	DN	Portata (L/min)
K- 07 15 00 13	230 V, 50 Hz	G 1/4	G 1/4	7	1250
K- 07 15 00 14	24 V DC	G 1/4	G 1/4	7	1250