


K-VSTO POM

Plugs

HANSA FLEX

Caratteristiche

Pressione di lavoro	0 - 16 bar (4 - 8 mm); 0 - 10 bar (10 - 28 mm)
Temperatura d'esercizio	-20 °C to +70 °C in air; +1 °C to +70 °C in water
Materiale	Acetalpolymerisat (POM)
Materiale di tenuta	NBR



Nota

Altri dati su richiesta.

Descrizione

Lightweight, push-in fittings distinguished by high strength, toughness, resistance to abrasion and impact resistance - ideal for a wide range of applications. Plastic and metal tubes are connected together quickly and easily. Suitable for compressed air or liquids, with good resistance to a large number of chemicals.

Articolo

Denominazione	Colore	L1 (mm)	Manicotto (mm)
K- 07 40 29 11	rosso	28,0	4
K- 07 40 29 12	rosso	28,0	5
K- 07 40 29 13	rosso	30,0	6
K- 07 40 29 14	rosso	31,0	8
K- 07 40 29 15	rosso	36,5	10
K- 07 40 29 16	rosso	38,5	12
K- 07 40 29 17	nero	45,0	15
K- 07 40 29 18	nero	41,5	18
K- 07 40 29 19	nero	45,0	22
K- 07 40 29 20	nero	56,0	28