K-SA MUFFE 16

Weld-on sleeve 16 made of black steel ST 37-2, DIN 2986 with continous thread

Caratteristiche

Pressione di lavoro	Max. 50 bar
Filettatura attacco	acc. ISO 7-1
Materiale	black steel ST 37-2



Nota

Altri dati su richiesta.

Descrizione

The steel fittings are made of tubular steel to DIN 2441 and boast good resistance to mechanical stresses.Hot dip galvanised steel fittings are completely coated with a layer of pure zinc and are therefore suitable for drinking water. they are also protected against rust.They are used in pipe construction, plumbing and gas installations as well as a wide range of industrial applications, especially in conjunction with the popular malleable iron series.

Articolo

Denominazione	Filetto	Lunghezza (mm)
K- 07 40 35 30	R 1/4	25,0
K- 07 40 35 33	R 3/8	26,0
K- 07 40 35 29	R 1/2	34,0
K- 07 40 35 32	R 3/4	36,0
K- 07 40 35 26	R 1	43,0
K- 07 40 35 28	R 1 1/4	48,0
K- 07 40 35 27	R 1 1/2	48,0
K- 07 40 35 31	R 2	56,0
K- 07 40 50 36	R 2 1/2	65,0
K- 07 40 50 37	R 3	71,0

Nonostante il più attento esame non si possono escludere eventuali errori ed omissioni, non ci assumiamo alcuna responsabilità per le indicazioni contenute.