


# K-STECKVERSCHR RU MINI

Male connectors, round, mini

**HANSA FLEX**

## Caratteristiche

Pressione di lavoro	Max. 10 bar, vacuum
Campo di impiego	Air, vacuum
Tubi flessibili consigliati	PU or PA (nylon)
Mezzi	Aria compressa
Norma	M thread acc. to DIN 13-1, with O-Ring G thread acc. to DIN EN ISO 228-1, with O-Ring R thread acc. to ISO 7-1, thread coating
Campo della temperatura:	0 °C to +60 °C
Superficie di tenuta	O-ring (NBR)
Materiale	Plastic, Nickel plated brass
Anello di compressione	Plastic



## Nota

Altri dati su richiesta.

## Descrizione

Push-in fittings series manufactured in plastic and nickel-plated brass, space-saving miniature design.

## Articolo

Denominazione	Filetto	per diametro esterno del tubo flessibile Ø mm	L1 (mm)
K- 07 40 23 67	M 3	3 mm	15,0
K- 07 40 23 68	M 3	4 mm	17,5
K- 07 40 23 69	M 5	3 mm	16,0
K- 07 40 23 70	M 5	4 mm	18,0
K- 07 40 23 71	M 5	6 mm	18,0
K- 07 40 23 72	M 6	3 mm	15,0
K- 07 40 23 73	M 6	4 mm	18,5
K- 07 40 23 74	M 6	6 mm	18,5
K- 07 40 23 75	M 7	4 mm	18,5
K- 07 40 23 76	M 7	6 mm	19,5
K- 07 40 23 77	G 1/8	4 mm	15,2
K- 07 40 23 78	G 1/8	6 mm	17,6
K- 07 40 23 79	R 1/8	4 mm	15,5
K- 07 40 23 80	R 1/8	6 mm	18,5