

# K-ABSPV AG OR

Shut-off valves, double parallel thread with O-ring

**HANSA FLEX**

## Caratteristiche

<b>Pressione di lavoro</b>	Max. 15 bar, coarse vacuum
<b>Campo di impiego</b>	Air, vacuum
<b>Tubi flessibili consigliati</b>	PU or PA (nylon)
<b>Mezzi</b>	Compressed air and all gases or liquids that are compatible with the materials
<b>Campo della temperatura:</b>	-20 °C to +80 °C
<b>Superficie di tenuta</b>	Parallel version: O-ring in housing, Conical version: thread coating
<b>Materiale</b>	Plastic, Nickel plated brass
<b>Anello di compressione</b>	Plastic



## Nota

Altri dati su richiesta.

## Descrizione

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

## Articolo

Denominazione	Filettatura 1	Filettatura 2	L1 (mm)	L2 (mm)	SW
K- 07 40 08 10	G 1/8	G 1/8	64,5	42,6	14 mm
K- 07 40 08 09	G 1/4	G 1/8	67,6	42,6	17 mm / 14 mm
K- 07 40 08 08	G 1/4	G 1/4	67,6	42,6	17 mm
K- 07 40 08 11	G 3/8	G 1/4	81,1	47,0	20 mm / 20 mm
K- 07 40 08 12	G 3/8	G 3/8	82,4	47,0	20 mm / 20 mm
K- 07 40 08 07	G 1/2	G 3/8	86,2	47,0	24 mm / 21 mm
K- 07 40 08 06	G 1/2	G 1/2	89,0	47,0	24 mm