


# K-W90 SVB POLYPROPYLETEN

Bulkhead elbow couplings - polypropylene

**HANSA FLEX**

## Caratteristiche

|                                |   |
|--------------------------------|---|
| <b>Pressione d'esercizio</b>   | Dependent on operating temperature: Max. 10 bar (at 20 °C); Max. 2.5 bar (at 90 °C) |
| <b>Materiale</b>               | Polypropylene (PP)  |
| <b>Temperatura d'esercizio</b> | Max. 90 °C  |



## Nota

Altri dati su richiesta.

## Descrizione

Chemically resistant to almost all inorganic acids and bases, even in high concentrations and at temperatures greater than 90 °C.

## Articolo

| Denominazione  | per flessibile | Filetto    | L1<br>(mm) | L2<br>(mm) | SW    |
|----------------|----------------|------------|------------|------------|-------|
| K- 07 40 41 75 | 4 mm / 6 mm    | M 10 x 1   | 43,0       | 25,0       | 14 mm |
| K- 07 40 41 76 | 6 mm / 8 mm    | M 14 x 1,5 | 53,0       | 33,0       | 19 mm |
| K- 07 40 41 77 | 8 mm / 10 mm   | M 16 x 1,5 | 58,0       | 36,0       | 22 mm |
| K- 07 40 41 78 | 9 mm / 12 mm   | M 18 x 1,5 | 67,0       | 43,0       | 24 mm |