

# K-SOFT PVC SET SVKM TUE NW7,2

Soft PVC workshop hose kits with quick disconnect couplings and stems DN 7.2

**HANSA FLEX**

## Caratteristiche

**Strato interno** Soft-PVC, black

**Inserzioni** Intreccio in poliestere

**Strato esterno** Soft-PVC, blue

**Temperatura d'esercizio** -20 °C to +60 °C



## Nota

Altri dati su richiesta.

## Descrizione

Highly flexible hose for compressed air applications in workshop areas. Assembled with brass stem and brass quick disconnect coupling DN 7.2

## Articolo

| Denominazione  | Ø tubo flessibile interno (mm) | Ø tubo flessibile esterno (mm) | pressione d'esercizio max. a 20°C (bar) | Lunghezza tubo flessibile (m) |
|----------------|--------------------------------|--------------------------------|---|-------------------------------|
| K- 07 10 11 91 | 6,3                            | 11,0                           | 15                                      | 5                             |
| K- 07 10 11 85 | 6,3                            | 11,0                           | 15                                      | 10                            |
| K- 07 10 11 87 | 6,3                            | 11,0                           | 15                                      | 15                            |
| K- 07 10 11 88 | 6,3                            | 11,0                           | 15                                      | 20                            |
| K- 07 10 11 90 | 6,3                            | 11,0                           | 15                                      | 25                            |
| K- 07 10 11 99 | 9,0                            | 14,5                           | 15                                      | 5                             |
| K- 07 10 11 93 | 9,0                            | 14,5                           | 15                                      | 10                            |
| K- 07 10 11 95 | 9,0                            | 14,5                           | 15                                      | 15                            |
| K- 07 10 11 96 | 9,0                            | 14,5                           | 15                                      | 20                            |
| K- 07 10 11 98 | 9,0                            | 14,5                           | 15                                      | 25                            |