

K-Y-STECK VERSCH DREH AG-K

Male branch Y-fittings, swivel type, conical male thread, coated

HANSA FLEX

Caratteristiche

| | |
|-----------------------------|--|
| Pressione di lavoro | Max. 15 bar, coarse vacuum |
| Campo di impiego | Air, vacuum |
| Tubi flessibili consigliati | PU or PA (nylon) |
| Mezzi | Compressed air and all gases or liquids that are compatible with the materials |
| Campo della temperatura: | -20 °C to +80 °C |
| Superficie di tenuta | Conical version: thread coating |
| Materiale | Plastic, Nickel plated brass |
| Anello di compressione | Plastic |



Nota

Altri dati su richiesta.

Descrizione

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

Articolo

| Denominazione | Filetto | per diametro esterno del tubo flessibile Ø mm | L1 (mm) | SW |
|----------------|---------|---|------------|-------|
| K- 07 40 03 31 | R 1/8 | 4 mm | 42,0 | 10 mm |
| K- 07 40 03 32 | R 1/8 | 6 mm | 43,5 | 12 mm |
| K- 07 40 03 33 | R 1/8 | 8 mm | 46,8 | 14 mm |
| K- 07 40 03 29 | R 1/8 | 10 mm | 56,0 | 17 mm |
| K- 07 40 03 30 | R 1/8 | 12 mm | 59,8 | 21 mm |
| K- 07 40 03 26 | R 1/4 | 4 mm | 45,0 | 14 mm |
| K- 07 40 03 27 | R 1/4 | 6 mm | 46,0 | 14 mm |
| K- 07 40 03 28 | R 1/4 | 8 mm | 48,8 | 14 mm |
| K- 07 40 03 24 | R 1/4 | 10 mm | 58,0 | 17 mm |
| K- 07 40 03 25 | R 1/4 | 12 mm | 61,8 | 21 mm |
| K- 07 40 03 37 | R 3/8 | 6 mm | 47,5 | 17 mm |
| K- 07 40 03 38 | R 3/8 | 8 mm | 50,3 | 17 mm |
| K- 07 40 03 34 | R 3/8 | 10 mm | 59,0 | 17 mm |
| K- 07 40 03 35 | R 3/8 | 12 mm | 62,8 | 21 mm |
| K- 07 40 03 36 | R 3/8 | 16 mm | 72,0 | 24 mm |
| K- 07 40 03 22 | R 1/2 | 6 mm | 51,0 | 21 mm |
| K- 07 40 03 23 | R 1/2 | 8 mm | 53,8 | 21 mm |
| K- 07 40 03 19 | R 1/2 | 10 mm | 62,5 | 21 mm |
| K- 07 40 03 20 | R 1/2 | 12 mm | 65,8 | 21 mm |
| K- 07 40 03 21 | R 1/2 | 16 mm | 75,0 | 24 mm |