

K-WERKST-SCHLAUCH SOFT

Workshop hose soft

HANSA FLEX

Caratteristiche

Strato interno Soft-PVC, black

Inserzioni Intreccio in poliestere

Strato esterno Soft-PVC, blue

Temperatura -20 °C to +60 °C

Lunghezza rullo 50 m



Nota

Altri dati su richiesta.

Descrizione

Highly flexible hose for compressed air applications in workshop areas (compressed air feed for pneumatic tools, equipping assembly stations, etc.). Thanks to the even fabric reinforcement, this hose combines high pressure resistance, very good handling and high mechanical strength with excellent bond adhesion. The high level of ozone resistance further enhances the hose's durability and reliability. TÜV approved.

Articolo

Denominazione	Ø tubo flessibile interno (mm)	Ø tubo flessibile esterno (mm)	Max. working pressure resistance at 23°C (bar)	Raggio di curvatura min. (mm)
K- 07 10 10 33	6,3	11,0	15	23
K- 07 10 10 34	8,0	13,0	15	28
K- 07 10 10 35	9,0	14,5	15	32
K- 07 10 10 36	10,0	15,5	15	35
K- 07 10 10 37	12,7	19,0	15	45
K- 07 10 10 38	16,0	23,0	15	56
K- 07 10 10 39	19,0	26,5	15	67
K- 07 10 10 40	25,0	33,5	15	88