

K-LKM S NW7,2 SCHL TUE

Safety couplings DN 7.2, with hose stem

HANSA FLEX

Caratteristiche

Pressione d'esercizio	0 - 35 bar, maximum static working pressure (non-pulsating)
Portata aria	1.100 l/min (at $\Delta p = 0.5$ bar)
Temperatura del fluido	-30 °C to +100 °C
Alloggiamento, bussola, corpo valvola	Nickel-plated brass
Molla, sfere	Stainless-steel
Materiale di tenuta	NBR



Nota

Altri dati su richiesta.

Descrizione

One-hand safety coupling with double locking mechanism. Connection: Similar to standard couplings, simply by pressing the plug into the coupling. Disconnection: The first locking mechanism is accessible when the sleeve is pushed back. The coupling valve closes. Air can then be relieved from the plug side (hose). The second locking mechanism is released by actuating the unlocking sleeve again. The coupling can now be disconnected.

Articolo

Denominazione	Attacco	Lunghezza (mm)	SW (mm)
K- 07 35 02 87	Stem, I.D. 6	60,0	22
K- 07 35 02 88	Stem, I.D. 8	60,0	22
K- 07 35 02 89	Stem, I.D. 9	60,0	22
K- 07 35 02 90	Stem, I.D. 10	60,0	22
K- 07 35 02 91	Stem, I.D. 13	60,0	22

Elementi supplementari

K-NIPPEL KUPPL NW7 AG VZ	Plugs for couplings DN 7.2 - DN 7.8, hardened, galvanised steel, male
K-NIPPEL KUPPL NW7 IG VZ 1	Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel, female
K-TUE 7,2 7,8 ST VZ 1	Stems for couplings DN 7.2 - DN 7.8, hardened, galvanised steel,