

K-DURCHGANGSVERTEILERDOSE

Through porting box with through-hole thread, PN 15

HANSA FLEX

Caratteristiche

| | |
|------------------------------------|--------------------------------|
| Pressione d'esercizio | Max. 15 bar |
| Coppia di rotazione fissaggio | 4 Nm |
| Coppia di rotazione filettatura MS | 12 Nm |
| Campo della temperatura: | -10 °C to +50 °C |
| Alloggiamento | Glass fibre-reinforced plastic |
| Filettatura | Brass |



Nota

Altri dati su richiesta.

Descrizione

1, 2 or 3-way porting boxes made of high-strength glass fibre-reinforced plastic for a wide range of applications. Available with up to 3 couplings and 2 inlet thread sizes. Optional through-hole thread at the bottom to facilitate the passage of the medium. All porting boxes have a robust, brass threaded insert for high tightening torques, TÜV certified. Suitable for almost any pneumatic application.

Articolo

| Denominazione | Filetto Entrata | Filettatura passante | Filetto dell'attacco |
|----------------|-----------------|----------------------|----------------------|
| K- 07 40 48 04 | G 1/2" | G 1/2 | 1 x G 1/2 |
| K- 07 40 48 05 | G 1/2" | G 1/2 | 2 x G 1/2 |
| K- 07 40 48 06 | G 1/2" | G 1/2 | 3 x G 1/2 |
| K- 07 40 48 07 | G 3/4" | G 3/4 | 1 x G 1/2 |
| K- 07 40 48 08 | G 3/4" | G 3/4 | 2 x G 1/2 |
| K- 07 40 48 09 | G 3/4" | G 3/4 | 3 x G 1/2 |