

# K-XG LOESBAR IG IG FLACHDICHT

Detachable double nipples, female, flat seat

**HANSA FLEX**

## Caratteristiche

|                     |                              |
|---------------------|------------------------------|
| Pressione di lavoro | Max. 10 bar                  |
| Filettatura esterna | Parallel to DIN EN ISO 228-1 |
| Filettatura interna | Parallel to DIN EN ISO 228-1 |
| Materiale           | Stainless steel 1.4408       |



## Nota

The dimensions of the standard screw fittings may change slightly during the life of the catalogue as a result of optimisation processes.  
Altri dati su richiesta.

## Articolo

| Denominazione  | Filetto | L1<br>(mm) | SW1<br>(mm) | SW2<br>(mm) |
|----------------|---------|------------|-------------|-------------|
| K- 07 40 45 85 | G 1/8   | 32,3       | 29          | 18          |
| K- 07 40 45 94 | G 1/4   | 32,4       | 29          | 18          |
| K- 07 40 45 95 | G 3/8   | 34,7       | 34          | 22          |
| K- 07 40 46 00 | G 1/2   | 40,0       | 39          | 26          |
| K- 07 40 46 01 | G 3/4   | 42,0       | 47          | 32          |
| K- 07 40 46 02 | G 1     | 48,7       | 58          | 40          |
| K- 07 40 46 03 | G 1 1/4 | 54,0       | 67          | 49          |
| K- 07 40 46 04 | G 1 1/2 | 58,9       | 76          | 56          |
| K- 07 40 46 05 | G 2     | 62,2       | 90          | 68          |