# K-SPIR SCHL KUPPL SET STANDARD

Spiral hose and coupling kit with standard coupling

## Caratteristiche

| | |
|---|---|
| **Applicazione** | Air, gases, oils, greases, fuels, organic and inorganic substances |
| **Temperatura d'esercizio** | -40 °C to +100 °C |
| **Tipo di attacco** | connection nipples and coupling NW 7,2 |



## Nota

Altri dati su richiesta.

## Descrizione

These hoses allow gaseous and liquid media to flow safely and efficiently (Air, gases, oils, greases, fuels, organic and inorganic substances). Thanks to their small coil diameter, they are compact, easy to handle and lightweight. Very good recoil force owing to the use of nylon 12 (PA).

## Articolo

| Denominazione | Ø tubo flessibile interno (mm) | Ø tubo flessibile esterno (mm) | Ø spirale esterno (mm) | Spire | Max. working pressure resistance at 23°C (bar) | lunghezza di lavoro max. (m) |
|---|---|---|---|---|---|---|
| **K- 07 10 12 95** | 6,3 | 7,9 | 75 | 15 | 13 | 2,5 |
| **K- 07 10 12 96** | 6,3 | 7,9 | 75 | 30 | 13 | 5,0 |
| **K- 07 10 12 97** | 6,3 | 7,9 | 75 | 45 | 13 | 7,5 |
| **K- 07 10 12 65** | 7,9 | 9,5 | 115 | 10 | 12 | 2,5 |
| **K- 07 10 12 66** | 7,9 | 9,5 | 115 | 20 | 12 | 5,0 |
| **K- 07 10 12 67** | 7,9 | 9,5 | 115 | 30 | 12 | 7,5 |
| **K- 07 10 12 68** | 9,5 | 11,8 | 140 | 8 | 11 | 2,5 |
| **K- 07 10 12 69** | 9,5 | 11,8 | 140 | 15 | 11 | 5,0 |
| **K- 07 10 12 70** | 9,5 | 11,8 | 140 | 23 | 11 | 7,5 |

## Accessori

| | |
|---|---|
| **K-DREHBARE VERSCHR KNICK** | Swivel adapters with kink protector |
| **K-STARRE VERSCHRAUBUNG** | Rigid adapters with kink protector |

*Nonostante il più attento esame non si possono escludere eventuali errori ed omissioni, non ci assumiamo alcuna responsabilità per le indicazioni contenute.*