

# K-SPIR SCHL KUPPL SET STANDARD

Spiral hose and coupling kit with standard coupling

**HANSA FLEX**

## Caratteristiche

<b>Applicazione</b>	Air, gases, oils, greases, fuels, organic and inorganic substances
<b>Temperatura d'esercizio</b>	-40 °C to +100 °C
<b>Tipo di attacco</b>	connection nipples and coupling NW 7,2



## Nota

Altri dati su richiesta.

## Descrizione

These hoses allow gaseous and liquid media to flow safely and efficiently (Air, gases, oils, greases, fuels, organic and inorganic substances). Thanks to their small coil diameter, they are compact, easy to handle and lightweight. Very good recoil force owing to the use of nylon 12 (PA).

## Articolo

Denominazione	Ø tubo flessibile interno (mm)	Ø tubo flessibile esterno (mm)	Ø spirale esterno (mm)	Spire	Max. working pressure resistance at 23°C (bar)	lunghezza di lavoro max. (m)
K- 07 10 12 95	6,3	7,9	75	15	13	2,5
K- 07 10 12 96	6,3	7,9	75	30	13	5,0
K- 07 10 12 97	6,3	7,9	75	45	13	7,5
K- 07 10 12 65	7,9	9,5	115	10	12	2,5
K- 07 10 12 66	7,9	9,5	115	20	12	5,0
K- 07 10 12 67	7,9	9,5	115	30	12	7,5
K- 07 10 12 68	9,5	11,8	140	8	11	2,5
K- 07 10 12 69	9,5	11,8	140	15	11	5,0
K- 07 10 12 70	9,5	11,8	140	23	11	7,5

## Accessori

<b>K-DREHBARE VERSCHR KNICK</b>	Swivel adapters with kink protector
<b>K-STARRE VERSCHRAUBUNG</b>	Rigid adapters with kink protector