

# K-SPIR SCHL KUPPL SET STAND MS

Spiral hose and coupling kit with standard coupling and push-in plug,  
bare brass

**HANSA FLEX**

## Caratteristiche

Tipo di attacco	connection nipples and coupling NW 7,2
Temperatura d'esercizio	-40 °C to +74 °C



## Nota

Altri dati su richiesta.

## Descrizione

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.

## Articolo

Denominazione	Ø tubo flessibile interno (mm)	Ø tubo flessibile esterno (mm)	Ø spira esterna (mm)	Max. working pressure resistance at 23°C (bar)	lunghezza di lavoro max. (m)
K-07 10 12 72	5,0	8,0	40	10	3,0
K-07 10 12 74	5,0	8,0	40	10	6,0
K-07 10 12 76	5,0	8,0	40	10	7,5
K-07 10 12 81	6,3	9,5	60	10	3,0
K-07 10 12 83	6,3	9,5	60	10	6,0
K-07 10 12 85	6,3	9,5	60	10	7,5
K-07 10 12 79	6,3	9,5	60	10	10,0
K-07 10 12 90	8,0	12,0	80	9	3,0
K-07 10 12 92	8,0	12,0	80	9	6,0
K-07 10 12 94	8,0	12,0	80	9	7,5
K-07 10 12 88	8,0	12,0	80	9	10,0

## Accessori

K-DREHBARE VERSCHRAUBUNG Swivel adapters