

# K-WERKST-SCHLAUCH SOFT O

Workshop hose soft, oil resistant

**HANSA FLEX**

## Caratteristiche

<b>Strato interno</b>	Soft-PVC, red, oil resistant
<b>Inserzioni</b>	Intreccio in poliestere
<b>Strato esterno</b>	Soft-PVC, black, oil resistant
<b>Temperatura</b>	-20 °C to +60 °C
<b>Lunghezza rullo</b>	50 m



## Nota

Altri dati su richiesta.

## Descrizione

Workshop hose to meet the most demanding requirements. Extremely flexible (even at low temperatures), good resistance to oil and chemicals, long service life and excellent resistance to mechanical stresses (deformation under pressure, bending cycles, pressure pulses).

## Articolo

Denominazione	Ø tubo flessibile interno (mm)	Ø tubo flessibile esterno (mm)	Max. working pressure resistance at 23°C (bar)	Raggio di curvatura min. (mm)
K- 07 10 10 41	6,3	11,0	16	18
K- 07 10 10 42	8,0	13,0	16	25
K- 07 10 10 43	9,0	14,5	16	25
K- 07 10 10 44	10,0	15,5	16	35
K- 07 10 10 45	12,7	19,0	16	50
K- 07 10 10 46	16,0	23,0	16	70
K- 07 10 10 47	19,0	26,5	16	70
K- 07 10 10 48	25,0	33,5	16	120