K-WERKST-SCHLAUCH SOFT O

Workshop hose soft, oil resistant

Caratteristiche

Strato interno	Soft-PVC, red, oil resistant
Inserzioni	Intreccio in poliestere
Strato esterno	Soft-PVC, black, oil resistant
Temperatura	-20 °C to +60 °C
Lunghezza rullo	50 m



Nota

Altri dati su richiesta.

Descrizione

Workshop hose to meet the most demanding requirements. Extremely flexible (even at low temperatures), good resistance to oil and chemicals, long service life and excellent resistance to mechanical stresses (deformation under pressure, bending cycles, pressure pulses).

Articolo

Denominazione	Ø tubo flessibile interno (mm)	Ø tubo flessibile esterno (mm)	Max. working pressure resistance at 23°C (bar)	Raggio di curvatura min. (mm)
K- 07 10 10 41	6,3	11,0	16	18
K- 07 10 10 42	8,0	13,0	16	25
K- 07 10 10 43	9,0	14,5	16	25
K- 07 10 10 44	10,0	15,5	16	35
K- 07 10 10 45	12,7	19,0	16	50
K- 07 10 10 46	16,0	23,0	16	70
K- 07 10 10 47	19,0	26,5	16	70
K- 07 10 10 48	25,0	33,5	16	120

Nonostante il più attento esame non si possono escludere eventuali errori ed omissioni, non ci assumiamo alcuna responsabilità per le indicazioni contenute.