


| Caratteristiche | | | | |
|-------------------------|------------------------------------|--|--|--|
| Attacco 1 | Filetto esterno metrico cilindrico | | | |
| Tenuta 1 | Cono interno da 24° | | | |
| Norma | ISO 8434-1 | | | |
| Materiale | Acciaio | | | |
| Protezione superficiale | con rivestimento elettrolitico | | | |





| Denominazione | DN | Size | pollice | per diametro esterno del tubo Ø | G1 | L1 |
|---------------|----|------|---------|---------------------------------|------------|------|
| | | | | (mm) | | (mm) |
| TR 04 HL | 5 | 3 | 3/16" | 6 | M 12 x 1,5 | 30 |
| TR 06 HL | 6 | 4 | 1/4" | 8 | M 14 x 1,5 | 31 |
| TR 08 HL 06 | 8 | 5 | 5/16" | 8 | M 14 x 1,5 | 38 |
| TR 08 HL | 8 | 5 | 5/16" | 10 | M 16 x 1,5 | 38 |
| TR 10 HL 08 | 10 | 6 | 3/8" | 10 | M 16 x 1,5 | 38 |
| TR 10 HL | 10 | 6 | 3/8" | 12 | M 18 x 1,5 | 39 |
| TR 13 HL | 12 | 8 | 1/2" | 15 | M 22 x 1,5 | 52 |