

# K-KOMPAKTZYL SCHWENKTISCH MSQ

Rotary actuator for compact cylinder MSQ

**HANSA FLEX**

## Caratteristiche

|                            |  |
|----------------------------|--|
| pressione d'esercizio max. | 0,7 MPa  |
| pressione d'esercizio min. | 0.10 MPa   |
| Esecuzione                 | rack and pinion  |
| Temperatura del fluido     | 0 °C to +60 °C   |
| Temperatura ambiente       | 0 °C to +60 °C   |
| Angolo di rotazione        | 0 to 190°  |
| Mezzi                      | Aria compressa   |
| Serie                      | MSQ  |
| Altri dati                 | narrow pivot table unit with low overall height<br>the rotation angle can be adjusted continuously<br>Positioning the housing allow for quick installation<br>the load can be mounted directly on the pivot table<br>Air connections of 2 pages possible |



## Articolo

| Denominazione  | Ø pistone (mm) | Attacco pneumatico | Dimensioni strutturali | Smorzamento                             | Peso per m (kg) |
|----------------|----------------|--------------------|------------------------|---|-----------------|
| K- 07 55 01 13 | 6              | M 3                | 1                      | without, with adjustment bolt           | 0,075           |
| K- 07 55 01 18 | 8              | M 5                | 2                      | without, with adjustment bolt           | 0,105           |
| K- 07 55 01 21 | 10             | M 5                | 3                      | elastic, with adjustment bolt           | 0,150           |
| K- 07 55 01 26 | 12             | M 5                | 7                      | elastic, with adjustment bolt           | 0,250           |
| K- 07 55 01 11 | 15             | M 5                | 10                     | elastic, with adjustment bolt           | 0,530           |
| K- 07 55 01 16 | 18             | M 5                | 20                     | elastic, with adjustment bolt           | 0,990           |
| K- 07 55 01 19 | 21             | G 1/8              | 30                     | elastic, with adjustment bolt           | 1,290           |
| K- 07 55 01 22 | 25             | G 1/8              | 50                     | elastic, with adjustment bolt           | 2,080           |
| K- 07 55 01 24 | 28             | G 1/8              | 70                     | elastic, with adjustment bolt           | 2,880           |
| K- 07 55 01 09 | 32             | G 1/8              | 100                    | elastic, with adjustment bolt           | 4,090           |
| K- 07 55 01 14 | 40             | G 1/8              | 200                    | elastic, with adjustment bolt           | 7,580           |
| K- 07 55 01 12 | 15             | M 5                | 10                     | elastic, with integrated shock absorber | 0,540           |
| K- 07 55 01 17 | 18             | M 5                | 20                     | elastic, with integrated shock absorber | 0,990           |
| K- 07 55 01 20 | 21             | G 1/8              | 30                     | elastic, with integrated shock absorber | 1,290           |
| K- 07 55 01 23 | 25             | G 1/8              | 50                     | elastic, with integrated shock absorber | 2,100           |
| K- 07 55 01 25 | 28             | G 1/8              | 70                     | elastic, with integrated shock absorber | 2,880           |
| K- 07 55 01 10 | 32             | G 1/8              | 100                    | elastic, with integrated shock absorber | 4,100           |
| K- 07 55 01 15 | 40             | G 1/8              | 200                    | elastic, with integrated shock absorber | 7,650           |