


K-SV 6 4 HOSTA

Bulkhead connectors Hosta

HANSA FLEX

Caratteristiche

Pressione d'esercizio	Max. 16 bar (at +20 °C)
Temperatura d'esercizio	-20 °C to +70 °C
Materiale	Ottone nichelato
Anello di compressione	Hostaform (black nickel-plated for Ø 10, 12)
O-ring	NBR, siliconefree
Pinza a trazione	Stainless steel AISI 316



Nota

Altri dati su richiesta.

Descrizione

Economy yet very high-quality series of push-in fittings made of nickel-plated brass. Compact, space-saving, lightweight design. An O-ring in the fillet at the end of the thread guarantees a tight connection for all male thread parts, even on rough surfaces.

Articolo

Denominazione	Filetto	per diametro esterno del tubo flessibile Ø mm	L1 (mm)	SW
K- 07 40 29 57	M 10 x 1	4 mm	32,0	13 mm
K- 07 40 29 58	M 14 x 1	6 mm	33,5	17 mm
K- 07 40 29 59	M 16 x 1	8 mm	37,0	18 mm
K- 07 40 29 60	M 17 x 1	10 mm	39,5	20 mm
K- 07 40 29 61	M 20 x 1	12 mm	42,0	24 mm