

LKM IR ST DK

Innesto rapido femmina (aria) con sistema di sicurezza

HANSA FLEX

Caratteristiche

Tipo	Manicotto femmina giunto di innesto rapido
Attacco 1	Filetto interno BSP cilindrico
Attacco 2	
Pressione d'esercizio	max. 12 bar
Portata aria	1.800 l/min (at 6 bar and $\Delta p = 1$ bar)
Temperatura del fluido	-20 °C to +70 °C
Alloggiamento	Aluminium, anodised
Filettatura	Nickel-plated brass
Parti interne	Stainless steel
Pulsante, valvola	Hardened, galvanised steel
Materiale di tenuta	NBR



Nota

Not suitable for hitting / pulsating tools.
Altri dati su richiesta.

Descrizione

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414.

Articolo

Denominazione	Filetto dell'attacco	Attacco	Lunghezza (mm)	SW (mm)
LKM 06 IR ST DK	G 1/4" -19	G 1/4 female	71,5	21
LKM 10 IR ST DK	G 3/8" -19	G 3/8 female	75,5	21
LKM 13 IR ST DK	G 1/2" -14	G 1/2 female	77,5	24