

K-PUR-BREMSSPIRALE

PUR brake coil with connection

HANSA FLEX

Savybės

1 + 2 jungtis	metrinis cilindrinis išorinis sriegis
Norma	tested in accordance with DIN 74323 DIN 74324 ISO 7268-2 ISO 7375-2 DIN 73378 DIN 74310-2
Leidimas	German Technical Surveyance Association (TÜV)- type approved (Certificate R 9910199)
Temperatūra min.	-40 °C
Temperatūra max.	90 °C
Medžiaga	PUR



Papildoma informacija

- will not break at fittings
- excellent antikink characteristics – kinking leaves no defects
- longer operation length
- highly resistant to tearing off at fittings
- excellent springback characteristics
- unplasticized so no embrittlement
- resistant to oil and grease
- resistant to UV and ozon
- service life many times longer than conventional coil tubing

Prekė

Pavadinimas	G1 + G2	Vidinis Ø (mm)	Išorinis Ø (mm)	Sienuelės storis (mm)	Ilgis (m)	Spalva
K- 07 10 13 21	M 16 x 1,5	8,0	12,0	2,0	4,50	juoda
K- 07 10 13 22	M 16 x 1,5	8,0	12,0	2,0	4,50	geltona
K- 07 10 13 23	M 16 x 1,5	8,0	12,0	2,0	4,50	raudona
K- 07 10 13 24	M 16 x 1,5	8,0	12,0	2,0	5,50	juoda
K- 07 10 13 25	M 16 x 1,5	8,0	12,0	2,0	5,50	geltona
K- 07 10 13 26	M 16 x 1,5	8,0	12,0	2,0	5,50	raudona