

# K-BIMETALLTHERMOMETER 52-2

Bimetallic thermometers

**HANSA FLEX**

## Savybės

Tipas	52
Rodmens korekcija	Trimming pointer
Darbinis slėgis	Max. 25 bar (on thermowell)
Taip pat pasirinkite	Thermowell (removable) with locking screw
Panardinimo velenas	Ø 8 mm, CrNi steel
Korpusas, žiedas	CrNi steel
Sandarinimo poveržlė	Flat instrument glass



## Nuoroda

Daugiau duomenų pagal užklausimą.

## Aprašas

Applications: Extremely versatile design for use in machine, vessel, pipeline and plant construction as well as for heating systems.

## Prekė

Pavadinimas	Indikatorių sritys	H Ø (mm)	Panardinimo veleno ilgis	Jungtis
K- 07 20 07 26	-30 °C to +50 °C	63,0	thermowell L1 = 63mm, L2 = 43mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 07 27	0 °C to +120 °C	63,0	thermowell L1 = 63mm, L2 = 43mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 07 28	0 °C to +160 °C	63,0	thermowell L1 = 63mm, L2 = 43mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 07 29	0 °C to +200 °C	63,0	thermowell L1 = 63mm, L2 = 43mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 07 30	0 °C to +250 °C	63,0	thermowell L1 = 63mm, L2 = 43mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 07 31	-30 °C to +50 °C	63,0	thermowell L1 = 100mm, L2 = 80mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 07 32	0 °C to +120 °C	63,0	thermowell L1 = 100mm, L2 = 80mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 07 33	0 °C to +160 °C	63,0	thermowell L1 = 100mm, L2 = 80mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 07 34	0 °C to +200 °C	63,0	thermowell L1 = 100mm, L2 = 80mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 07 35	0 °C to +250 °C	63,0	thermowell L1 = 100mm, L2 = 80mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 07 36	-30 °C to +50 °C	63,0	thermowell L1 = 160mm, L2 = 140mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 07 37	0 °C to +120 °C	63,0	thermowell L1 = 160mm, L2 = 140mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 07 38	0 °C to +160 °C	63,0	thermowell L1 = 160mm, L2 = 140mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 02 11	-30 °C to +50 °C	100,0	thermowell L1 = 63mm, L2 = 43mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 02 12	0 °C to +120 °C	100,0	thermowell L1 = 63mm, L2 = 43mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 02 13	0 °C to +160 °C	100,0	thermowell L1 = 63mm, L2 = 43mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 02 14	0 °C to +250 °C	100,0	thermowell L1 = 63mm, L2 = 43mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 02 15	-30 °C to +50 °C	100,0	thermowell L1 = 100mm, L2 = 80mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 02 16	0 °C to +120 °C	100,0	thermowell L1 = 100mm, L2 = 80mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 02 17	0 °C to +160 °C	100,0	thermowell L1 = 100mm, L2 = 80mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 02 18	0 °C to +200 °C	100,0	thermowell L1 = 100mm, L2 = 80mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 02 19	0 °C to +250 °C	100,0	thermowell L1 = 100mm, L2 = 80mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 02 20	-30 °C to +50 °C	100,0	thermowell L1 = 160mm, L2 = 140mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 02 21	0 °C to +120 °C	100,0	thermowell L1 = 160mm, L2 = 140mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 02 22	0 °C to +160 °C	100,0	thermowell L1 = 160mm, L2 = 140mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 02 23	0 °C to +200 °C	100,0	thermowell L1 = 160mm, L2 = 140mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 02 24	0 °C to +250 °C	100,0	thermowell L1 = 160mm, L2 = 140mm	Flush, with collar for thermowell, Ø 18 mm

## Priedai

K-SCHUTZROHRE EINSCHRAUB	Screw-in thermowells
K-SCHUTZROHRE EINSCHWEISS	Weld-in thermowells