

K-MANO 1

Pressure gauges (CrNi steel type / safety housing)

HANSA FLEX

Savybės

Tipas	232.30
Konstrukcija	Bourdon-tube pressure gauge, CrNi steel type, with solid baffle wall and blow-out (safety housing)
Panaudojimas	For gaseous or liquid, corrosive and crystallising media which do not have high viscosity, also in corrosive atmosphere
Kokybės klasė	1,6 (Ø 63 mm), 1,0 (Ø 100 mm)
Medžiagos temperatūra	max. +200 °C
Aplinkos temperatūra	-40 °C to +60 °C
Korpusas	CrNi steel
Sandarinio poveržlė	Laminated safety glass Ø 63 = Polycarbonate



Nuoroda

Daugiau duomenų pagal užklausimą.

Aprašas

Safety version with more fracture-resistant separating wall

Prekė

Pavadinimas	Matavimo sritis	H Ø (mm)	Jungtis
K- 07 20 07 15	-1 / 0.0 bar	63,0	G 1/4"
K- 07 20 07 16	0 - 1.6 bar	63,0	G 1/4"
K- 07 20 07 17	0 - 2.5 bar	63,0	G 1/4"
K- 07 20 07 18	0 - 4.0 bar	63,0	G 1/4"
K- 07 20 07 19	0 - 6.0 bar	63,0	G 1/4"
K- 07 20 07 20	0 - 10.0 bar	63,0	G 1/4"
K- 07 20 07 21	0 - 16.0 bar	63,0	G 1/4"
K- 07 20 07 22	0 - 25.0 bar	63,0	G 1/4"
K- 07 20 07 23	0 - 40.0 bar	63,0	G 1/4"
K- 07 20 07 24	0 - 60.0 bar	63,0	G 1/4"
K- 07 20 07 25	0 - 100.0 bar	63,0	G 1/4"
K- 07 20 01 97	0 - 1.0 bar	100,0	G 1/2"
K- 07 20 01 98	0 - 1.6 bar	100,0	G 1/2"
K- 07 20 01 99	0 - 2.5 bar	100,0	G 1/2"
K- 07 20 02 00	0 - 4.0 bar	100,0	G 1/2"
K- 07 20 02 01	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 02 02	0 - 10.0 bar	100,0	G 1/2"
K- 07 20 02 03	0 - 16.0 bar	100,0	G 1/2"
K- 07 20 02 04	0 - 25.0 bar	100,0	G 1/2"
K- 07 20 02 05	0 - 40.0 bar	100,0	G 1/2"
K- 07 20 02 06	0 - 60.0 bar	100,0	G 1/2"
K- 07 20 02 07	0 - 100.0 bar	100,0	G 1/2"
K- 07 20 02 08	0 - 160.0 bar	100,0	G 1/2"
K- 07 20 02 09	0 - 250.0 bar	100,0	G 1/2"
K- 07 20 02 10	0 - 400.0 bar	100,0	G 1/2"