
K-MANO ABSPH MUF ZAPF

Pressure gauge stopcocks, female - male

Savybės

Panaudojimas	For all pressure gauges with a flat gasket acc. to DIN 16258
Slėgio diapazonas	Max. 16 bar, depending on the variantPressure gauge valves should be used for higher pressures
Temperatūra	Max. +50 °C
Korpusas	Brass with a bare metal surface or stainless steel 1.4571
Rankena	Plastic
Patikros jungė	-



Nuoroda

K-07201090, K-07201091 in acc. with DIN 16261-A, K-07201096, K-07201097 in acc. with DIN 16261-B
K-07201128, K-07201129 in acc. with DIN 16262-A, K-07201127 in acc. with DIN 16262-B
Daugiau duomenų pagal užklausimą.

Aprašas

It is useful to install a stopcock as a shut-off element between the pressure gauge and the pipe. When the lever is set to the »blow out« position, the medium is discharged into the atmosphere. Stopcocks with a test port allow pressure gauges to be simultaneously connected to the pipe.

Papildoma informacija

Further measuring ranges on request
Version for panel mounting available on request. Version with max. pointer available on request

Prekė

Pavadinimas	Sriegis	PN (bar)	SW (mm)	Medžiaga
K- 07 20 10 94	G 1/4	6	17	žalvaris
K- 07 20 10 95	G 3/8	16	22	žalvaris
K- 07 20 10 97	G 1/2	25	27	žalvaris
K- 07 20 10 96	G 1/2	25	27	Stainless steel
K- 07 20 10 98	G 1/2	25	27	žalvaris