

K-RMM U KUNSTSTOFF MZ

Standard pressure gauges, connection radial on bottom

HANSA FLEX

Savybės

Tipas	111.10 (radial connector on bottom)
Konstrukcija	Bourdon-tube pressure gauge in standard design
Panaudojimas	gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise
Kokybės klasė	1.6 (Art No. K-07200303, K-07403298 - K-07201188: 2.5)
Markės rodmuo	(for Ø 160 mm - red pointer on the scale) red pointer to the window. For measuring ranges 0...0,6 bar bis 0...60 bar
Medžiagos temperatūra	maks. +60 °C
Aplinkos temperatūra	nuo -20 °C iki +60 °C
Korpusas	Plastic
Matuoklio dalies medžiaga ir rodyklės	Vario lydinys
Sandarinimo poveržlė	Transparent plastic



Nuoroda

Daugiau duomenų pagal užklausimą.

Prekė

Pavadinimas	Matavimo sritis	H Ø (mm)	Jungtis
K- 07 20 03 03	-1200 / 0.0 mbar	100,0	G 1/2"
K- 07 20 03 04	-1 / 0.0 bar	100,0	G 1/2"
K- 07 20 03 05	-1 / +0.6 bar	100,0	G 1/2"
K- 07 20 03 06	-1 / +1.5 bar	100,0	G 1/2"
K- 07 20 03 07	-1 / +3.0 bar	100,0	G 1/2"
K- 07 20 03 08	-1 / +5.0 bar	100,0	G 1/2"
K- 07 20 03 09	-1 / +9.0 bar	100,0	G 1/2"
K- 07 20 02 84	0 - 0.6 bar	100,0	G 1/2"
K- 07 20 02 85	0 - 1.0 bar	100,0	G 1/2"
K- 07 20 02 86	0 - 1.6 bar	100,0	G 1/2"
K- 07 20 02 87	0 - 2.5 bar	100,0	G 1/2"
K- 07 20 02 88	0 - 4.0 bar	100,0	G 1/2"
K- 07 20 02 89	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 02 90	0 - 10.0 bar	100,0	G 1/2"
K- 07 20 02 91	0 - 16.0 bar	100,0	G 1/2"
K- 07 20 02 92	0 - 25.0 bar	100,0	G 1/2"
K- 07 20 02 93	0 - 40.0 bar	100,0	G 1/2"
K- 07 20 11 86	0 - 60.0 bar	100,0	G 1/2"
K- 07 20 11 87	0 - 100.0 bar	100,0	G 1/2"
K- 07 20 11 88	0 - 160.0 bar	100,0	G 1/2"