

K-TR PA 12 ROLLE

Plastic pipes on coils, polyamide PA 12

HANSA FLEX

Savybės

Darbinė temperatūra -60 °C to +100 °C (PA 12)

Savybės Resistant to corrosion, vibration, impact, ageing, high pressures and heat

Medžiaga Polyamid PA 12, hard (according to DIN 73378)



Nuoroda

Operating pressure with 2.5 x overpressure safety!

Daugiau duomenų pagal užklausimą.

Aprašas

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

Prekė

| Pavadinimas | Žarnos Ø viduje (mm) | Žarnos Ø išorėje (mm) | maks. eksploatacinis slėgis esant 20 °C (bar) | Ritinio ilgis (m) |
|----------------|----------------------|-----------------------|---|-------------------|
| K- 07 10 04 77 | 9,0 | 12,0 | 19 | 25 |
| K- 07 10 04 79 | 12,0 | 15,0 | 15 | 25 |
| K- 07 10 04 81 | 14,0 | 18,0 | 16 | 25 |
| K- 07 10 04 83 | 18,0 | 22,0 | 14 | 25 |
| K- 07 10 04 76 | 9,0 | 12,0 | 19 | 100 |
| K- 07 10 04 78 | 12,0 | 15,0 | 15 | 100 |
| K- 07 10 04 80 | 14,0 | 18,0 | 16 | 100 |
| K- 07 10 04 82 | 18,0 | 22,0 | 14 | 100 |
| K- 07 10 04 84 | 23,0 | 28,0 | 14 | 50 |