

K-TR PA 12 ROLLE

Plastic pipes on coils, polyamide PA 12

HANSA FLEX

Savybės

Darbinė temperatūra -60 °C to +100 °C (PA 12)

Savybės Resistant to corrosion, vibration, impact, ageing, high pressures and heat

Medžiaga Polyamid PA 12, hard (according to DIN 73378)



Nuoroda

Operating pressure with 2.5 x overpressure safety!

Daugiau duomenų pagal užklausimą.

Aprašas

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

Prekė

Pavadinimas	Žarnos Ø viduje (mm)	Žarnos Ø išorėje (mm)	maks. eksploatacinis slėgis esant 20 °C (bar)	Ritinio ilgis (m)
K- 07 10 04 77	9,0	12,0	19	25
K- 07 10 04 79	12,0	15,0	15	25
K- 07 10 04 81	14,0	18,0	16	25
K- 07 10 04 83	18,0	22,0	14	25
K- 07 10 04 76	9,0	12,0	19	100
K- 07 10 04 78	12,0	15,0	15	100
K- 07 10 04 80	14,0	18,0	16	100
K- 07 10 04 82	18,0	22,0	14	100
K- 07 10 04 84	23,0	28,0	14	50