

# K-TR PA 12 ROLLE

Plastic pipes on coils, polyamide PA 12

**HANSA FLEX**

## Savybės

**Darbinė temperatūra** -60 °C to +100 °C (PA 12)

**Savybės** Resistant to corrosion, vibration, impact, ageing, high pressures and heat

**Medžiaga** Polyamid PA 12, hard (according to DIN 73378)



## Nuoroda

Operating pressure with 2.5 x overpressure safety!

Daugiau duomenų pagal užklausimą.

## Aprašas

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

## Prekė

| Pavadinimas    | Žarnos Ø viduje<br>(mm) | Žarnos Ø išorėje<br>(mm) | maks. eksploatacinis slėgis esant 20 °C<br>(bar) | Ritinio ilgis<br>(m) |
|----------------|-------------------------|--------------------------|--|----------------------|
| K- 07 10 04 77 | 9,0                     | 12,0                     | 19   | 25                   |
| K- 07 10 04 79 | 12,0                    | 15,0                     | 15   | 25                   |
| K- 07 10 04 81 | 14,0                    | 18,0                     | 16   | 25                   |
| K- 07 10 04 83 | 18,0                    | 22,0                     | 14   | 25                   |
| K- 07 10 04 76 | 9,0                     | 12,0                     | 19   | 100                  |
| K- 07 10 04 78 | 12,0                    | 15,0                     | 15   | 100                  |
| K- 07 10 04 80 | 14,0                    | 18,0                     | 16   | 100                  |
| K- 07 10 04 82 | 18,0                    | 22,0                     | 14   | 100                  |
| K- 07 10 04 84 | 23,0                    | 28,0                     | 14   | 50                   |