

K-SPIR SCHL KUPPL SET

Spiral hose and coupling kits


HANSA FLEX

Savybės

Darbinis slėgis max. 10 bar (to the temperature +20 °C); max. 7 bar (at temperature +40 °C); max. 5 bar (at temperature +60 °C)

Mova High quality hand quick release coupling of steel for high flow rates
For demanding applications with high mechanical wear

Spiralinė žarna Polyurethane



Nuoroda

Daugiau duomenų pagal užklausimą.

Aprašas

For pneumatic applications in challenging industrial environments. High-quality, one-hand quick disconnect coupling made of steel with safety lock to prevent unintentional disconnection. For complex applications susceptible to severe mechanical wear. The outer layer of the hose, which is designed to withstand flying sparks and scorching, has special spark protection. It is therefore ideal for all pneumatic tools used in welding processes.

Prekė

| Pavadinimas | Žarnos matmuo | Spiralės Ø (mm) | Darbinis ilgis (m) |
|----------------|----------------|--------------------|-----------------------|
| K- 07 10 07 56 | 10 mm x 6,5 mm | 52 | 4,0 |
| K- 07 10 07 57 | 10 mm x 6,5 mm | 52 | 6,0 |
| K- 07 10 07 58 | 12 mm x 8 mm | 65 | 8,0 |