

K-VSEH 3-KRAFT

Receptacle combinations »3-Kraft«

HANSA FLEX

Savybės

Korpusas	Amaplast with hinged cover
Integruotas korpuse	Hanging eyelets, wall mounting fixing and standing feet
Konstrukcija	Pre-wired
Linijos įvadai	Top: 1 x M 32, 1 x M 25, 2 x M 20; Side: 1 x M 25; One opening at the top for pneumatic connection or grabrails (all introductions to break)
Apsaugos rūšis	IP 44



Nuoroda

Daugiau duomenų pagal užklausimą.

Aprašas

Receptacle combination with low power, high power or combined connections. Equipped with a pneumatic connection (DN 7.2 coupling with 9 mm stem).

Prekė

Pavadinimas	Komponentai	Spalva
K- 07 10 03 50	3 Schuko socket 16 A 2p + E 230 V	geltona
K- 07 10 03 49	2 Schuko socket 16 A 2p + E 230 V, 1 CEEform socket 16 A 5p 400 V	sidabras

Priedai

K-VT 2 KUPPL 7,2 STECKNIP MS	Distributors with 2 quick disconnect couplings DN 7.2, brass with push in plug DN 7.2 - DN 7.8
K-ZUBEH VSEH 3 KRAFT AIRKRAFT	Accessories for receptacle combinations »3-Kraft« and »airkraft«