

# K-VERSCHLUSSNIPPEL IG MS

Self-sealing plugs, brass

**HANSA FLEX**

## Savybės

|  |   |
|--|---|
| Darbinis slėgis                                    | See table. All values referred to a medium temperature of 50 °C (static working pressure)   |
| Oro srautas  | 440 l/min (G 1/8), 840 l/min (G 1/4),<br>1.280 l/min (G 3/8),<br>1.950 l/min (G 1/2), 4.500 l/min (G 3/4) (at 6 bar and $\Delta p = 0,5$ bar) |
| Medžiagos temperatūra                              | -20 °C to +100 °C   |
| Korpusas, mova, vožtuvas                           | Brass   |
| Spyruoklė, spyruoklinis atraminis žiedas, rutuliai | stain less steel  |
| Sandarinimo medžiaga                               | NBR   |



## Nuoroda

Daugiau duomenų pagal užklausimą.

## Aprašas

Hydraulic couplings, both sides sealing, for liquid media acc. to ISO 7241, B Series.

## Prekė

| Pavadinimas    | Jungtis      | NW   | Darbinis slėgis (bar) | Ilgis (mm) | SW (mm) |
|----------------|--------------|------|-----------------------|------------|---------|
| K- 07 40 10 15 | G 1/8 female | 4,3  | 250,0                 | 29,5       | 14      |
| K- 07 40 10 16 | G 1/4 female | 6,3  | 200,0                 | 35,3       | 19      |
| K- 07 40 10 17 | G 3/8 female | 7,5  | 200,0                 | 39,0       | 22      |
| K- 07 40 10 18 | G 1/2 female | 11,0 | 150,0                 | 48,0       | 27      |
| K- 07 40 10 19 | G 3/4 female | 13,0 | 100,0                 | 60,0       | 36      |