

K-HYDR-KUPPLUNG IG POM

Hydraulic couplings, POM

HANSA FLEX

Savybės

Darbinis slėgis	See table. All values referred to a medium temperature of 50 °C (static working pressure)
Oro srautas	440 l/min (G 1/8), 840 l/min (G 1/4), 1.280 l/min (G 3/8), 1.950 l/min (G 1/2), 4.500 l/min (G 3/4) (at 6 bar and $\Delta p = 0,5$ bar)
Medžiagos temperatūra	-20 °C to +90 °C
Korpusas, mova	POM (Delrin), white
Vožtuvas	Stainless steel 1.4305
Spyruoklė, spyruoklinis atraminis žiedas, rutuliai	stain less steel
Sandarinimo medžiaga	NBR



Nuoroda

Daugiau duomenų pagal užklausimą.

Aprašas

Hydraulic couplings, both sides sealing, for liquid media acc. to ISO 7241, B Series.

Prekė

Pavadinimas	Jungtis	Darbinis slėgis (bar)	Ilgis (mm)	NW	SW (mm)
K- 07 35 03 76	G 1/8 female	15,0	48,5	4,3	14
K- 07 35 03 77	G 1/4 female	15,0	57,6	6,0	19
K- 07 35 03 78	G 3/8 female	15,0	64,2	7,5	22
K- 07 35 03 79	G 1/2 female	10,0	76,0	11,0	27
K- 07 35 03 80	G 3/4 female	10,0	96,0	13,0	34