
K-LKM 5 UWB

Non-interchangeable quick disconnect couplings DN 5

Savybės

Darbinis slėgis	0 - 35 bar, maximum static working pressure (non-pulsating)
Oro srautas	560 l/min (at 6 bar and Δp = 0.5 bar)
Medžiagos temperatūra	-20 °C to +100 °C
Atblokavimo įvorė	Anodised aluminium
Spyruoklė, spyruoklinis atraminis žiedas, rutuliai	stain less steel
Sandarinimo medžiaga	NBR



Nuoroda

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings.
Daugiau duomenų pagal užklausimą.

Aprašas

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

Prekė

Pavadinimas	Jungtis	Spalva	Ilgis (mm)	SW (mm)
K- 07 35 06 80	G 1/8 male	žalia	45,0	14
K- 07 35 06 81	G 1/4 male	žalia	47,0	17
K- 07 35 06 82	G 1/8 female	žalia	45,0	14
K- 07 35 06 83	G 1/4 female	žalia	47,0	17
K- 07 35 06 84	G 1/8 male	Brown	45,0	14
K- 07 35 06 85	G 1/4 male	Brown	47,0	17
K- 07 35 06 86	G 1/8 female	Brown	45,0	14
K- 07 35 06 87	G 1/4 female	Brown	47,0	17
K- 07 35 06 88	G 1/8 male	mėlyna	45,0	14
K- 07 35 06 89	G 1/4 male	mėlyna	47,0	17
K- 07 35 06 90	G 1/8 female	mėlyna	45,0	14
K- 07 35 06 91	G 1/4 female	mėlyna	47,0	17
K- 07 35 06 92	G 1/8 male	raudona	45,0	14
K- 07 35 06 93	G 1/4 male	raudona	47,0	17
K- 07 35 06 94	G 1/8 female	raudona	45,0	14
K- 07 35 06 95	G 1/4 female	raudona	47,0	17

Nepaisant kruopštaus patikrinimo, negalime atmesti klaidų tikimybės, todėl už esamus duomenis neatsakome.