

K-LKM 7,8 UWB

Non-interchangeable quick disconnect couplings DN 7.8

HANSA FLEX

Savybės

Darbinis slėgis	0 - 35 bar, maximum static working pressure (non-pulsating)
Oro srautas	1.800 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Medžiagos temperatūra	-20 °C to +100 °C
Korpusas	Brass
Vožtuvas	Die-cast zinc, nickel-plated
Atblokavimo įvorė	Anodised aluminium
Spyruoklė, spyruoklinis atraminis žiedas, rutuliai	stain less steel
Sandarinimo medžiaga	NBR



Nuoroda

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings.

Daugiau duomenų pagal užklausimą.

Aprašas

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

Prekė

Pavadinimas	Jungtis	Spalva	Ilgis (mm)	SW (mm)
K- 07 35 08 01	G 1/4 male	žalia	57,5	19
K- 07 35 08 02	G 3/8 male	žalia	57,5	19
K- 07 35 08 03	G 1/4 female	žalia	55,5	19
K- 07 35 08 04	G 3/8 female	žalia	54,5	19
K- 07 35 08 05	G 1/4 male	Brown	57,5	19
K- 07 35 08 06	G 3/8 male	Brown	57,5	19
K- 07 35 08 07	G 1/4 female	Brown	55,5	19
K- 07 35 08 08	G 3/8 female	Brown	54,5	19
K- 07 35 08 09	G 1/4 male	mėlyna	57,5	19
K- 07 35 08 10	G 3/8 male	mėlyna	57,5	19
K- 07 35 08 11	G 1/4 female	mėlyna	55,5	19
K- 07 35 08 12	G 3/8 female	mėlyna	54,5	19
K- 07 35 08 13	G 1/4 male	raudona	57,5	19
K- 07 35 08 14	G 3/8 male	raudona	57,5	19
K- 07 35 08 15	G 1/4 female	raudona	55,5	19
K- 07 35 08 16	G 3/8 female	raudona	54,5	19