

# K-BALGGREIFER 2,5 SILIKON

Bellows suction pads, round, 2.5 folds, material silicone

**HANSA FLEX**

## Savybės

**Savybės** Soft, flexible folds  
Soft, tapered sealing lips  
Support surfaces on the bottom  
high suction power  
optimum damping effect  
very good adaptation to curved or uneven material

**Taikymo sritis** Handling of highly uneven parts (e.g.tubes)  
Handling of highly sensitive parts



## Nuoroda

Mini-sensor with housing and connection cable, analogue or digital output signal. Minimum size and low weight combined with high measuring accuracy. Daugiau duomenų pagal užklausimą.

## Aprašas

Robust and hard-wearing suction pad with a single sealing lip. Used wherever objects (parts, packing materials, etc.) need to be lifted, transported, turned over or handled in some other manner. It is also ideal when it is necessary to compensate varying workpiece heights or uneven surfaces or to handle easily damaged parts. It acts as the connecting element between the vacuum generator and the workpiece.

## Papildoma informacija

Attention: The price does not include connection nipples. Please order separately.

## Prekė

Pavadinimas	Prijungimo įmovos sriegiai išorėje	Prijungimo įmovos sriegiai viduje	Aukštis su įmovos sriegiais išorėje	Aukštis su įmovos sriegiais viduje	H Ø (mm)
K- 07 45 00 46	K-07450001	K-07450005	18,5	23,5	5,0
K- 07 45 00 48	K-07450002 / K-07450004	K-07450007	19 / 20	26	7,0
K- 07 45 00 50	K-07450002 / K-07450004	K-07450007	20 / 21	27	9,0
K- 07 45 00 52	K-07450002 / K-07450004	K-07450007	26 / 27	33	12,0
K- 07 45 00 54	K-07450002 / K-07450004	K-07450007	27 / 28	34	14,0
K- 07 45 00 56	K-07450002 / K-07450004	K-07450007	27 / 28	34	18,0
K- 07 45 00 58	K-07450002 / K-07450004	K-07450007	27 / 28	34	20,0
K- 07 45 00 60	K-07450004	K-07450007	40	46	25,0
K- 07 45 00 62	K-07450003	K-07450006	41,5	52,5	32,0
K- 07 45 00 64	K-07450003	K-07450006	50	61	42,0
K- 07 45 00 66	K-07450003	K-07450006	53	64	52,0

## Priedai

**K-ANSCHLUSSNIP BALGSAUGER** Connection nipples for bellows suction pads, round, 1.5 and 2.5 folds