

K-FEDERSTOESSEL

Spring plungers

HANSA FLEX

Savybės

Panaudojimas	Handling of workpieces with differing heights (eg. Curved metal sheets) Handling of very sensitive workpieces, very soft landing is assured
Temperatūra min.	0 °C
Temperatūra max.	80 °C
Siurbtuko jungtis	M 3 female
Konstrukcija	Spring plunger with high-strength steel rod, guide sleeve and lower damping spring Plunger rod with integrated vacuum guide
Spyruoklės eiga	5,0 mm



Nuoroda

Daugiau duomenų pagal užklausimą.

Aprašas

Suitable for all round or oval suction pads in our standard range.

Prekė

Pavadinimas	Vakuumo jungtis	Ilgis (mm)	Vertikalioji apkrova (N/m ²)
K- 07 45 00 73	M 3 female	33,5	550
K- 07 45 00 76	M 5 female	41,2	1500
K- 07 45 00 74	M 5 female	47,2	1500
K- 07 45 00 75	M 5 female	59,2	1500
K- 07 45 00 70	G 1/8 female	80,0	3700
K- 07 45 00 67	G 1/8 female	95,0	3700
K- 07 45 00 71	G 1/8 female	93,0	3700
K- 07 45 00 68	G 1/8 female	124,5	2400
K- 07 45 00 72	G 1/8 female	124,0	2400
K- 07 45 00 69	G 1/8 female	154,0	2400