K-DRS MDR 5 M ENTLASTU VENT

»MDR 5« pressure switches, with unloading valve / on/off switch / flange 1/4, without motor protection circuit

Savybės

Medžiagos temperatūra	-5 °C to +80 °C
maks. išjungimo slėgis	16 bar
Paskirstymo pajėgumas	5,5 kW
Kontakto rūšis	NC (3-pole)
maks. komutavimų dažnis	120 (electrical), 600 (mechanical)
Apsaugos rūšis	IP 54



Nuoroda

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)
Daugiau duomenų pagal užklausimą.

Aprašas

Three-phase version

užsakymo nuorodos

For use on devices that have to be vented whenever they are turned off, either because of safety regulations or for technical reasons. The pneumatic devices are disconnected from the system and simultaneously vented each time they are shut off.

Papildoma informacija

Important: A thermal, 3-pole overcurrent relay must be ordered together with these switches. Without this relay, the on/off mechanism does not work.

Prekė

Pavadinimas	Suslėgtojo oro jungtis	Nustatymo diapazonas
K- 07 30 24 25	G 1/2	2,0 - 11,0 bar
K- 07 30 24 27	G 1/2	2,5 - 16,0 bar