

# K-BKR LEICHT IG AG

Ball valves, lightweight type, female/male thread

**HANSA FLEX**

## Savybės

|                               |  |
|-------------------------------|--|
| <b>Taikymo sritis</b>         | Compressed air, water, non-toxic and non-corrosive gases, heating systems, agriculture |
| <b>Darbinis slėgis</b>        | Max. 40 bar  |
| <b>Darbinė temperatūra</b>    | -15 °C to +90 °C   |
| <b>Sriegių aprašas</b>        | G thread acc. DIN EN ISO 228-1   |
| <b>Korpusas</b>               | Nickel-plated brass  |
| <b>Svirtis</b>                | Alu, painted black   |
| <b>Kūgis</b>                  | Chrome-plated brass  |
| <b>Rutulio sandariklis</b>    | PTFE   |
| <b>Velenėlio sandarinimas</b> | HNBR / EPDM / PTFE. 2 O-Rings (HNBR / EPDM) 1 gasket (PTFE)<br>additional PTFE-gasket  |



## Nuoroda

Daugiau duomenų pagal užklausimą.

## Prekė

| Pavadinimas    | DN | Sriegis | A<br>(mm) | B<br>(mm) | L<br>(mm) |
|----------------|----|---------|-----------|-----------|-----------|
| K- 07 30 00 25 | 8  | G 1/4   | 85,0      | 42,0      | 44,0      |
| K- 07 30 00 26 | 10 | G 3/8   | 85,0      | 42,0      | 51,0      |
| K- 07 30 00 27 | 15 | G 1/2   | 85,0      | 46,0      | 60,0      |
| K- 07 30 00 28 | 20 | G 3/4   | 105,0     | 53,0      | 70,0      |
| K- 07 30 00 29 | 25 | G 1     | 105,0     | 57,0      | 79,0      |
| K- 07 30 00 30 | 32 | G 1 1/4 | 130,0     | 70,0      | 91,0      |
| K- 07 30 00 31 | 40 | G 1 1/2 | 130,0     | 76,0      | 104,0     |
| K- 07 30 00 32 | 50 | G 2     | 165,0     | 92,0      | 122,0     |