

# K-3 BKR STELLANTR D L MS

Brass ball valves, 3-way, with double-acting actuator, L-bore

**HANSA FLEX**

## Savybės

<b>Konstrukcija</b>	Pneumatic actuators, in double- or single acting version, with integrated end-position feedback
<b>Kiaurymė</b>	„L“ formos
<b>Darbinė temperatūra</b>	-20 °C to +70 °C
<b>Sukimo kampas</b>	90 °
<b>Valdymo slėgis</b>	5.5 bar
<b>Vožtuvo adapteris</b>	Supplied as standard
<b>Pavara</b>	aluminium eloxed
<b>Pavaros sandariklis</b>	NBR
<b>Rutulinis vožtuvas</b>	Chrome-plated brass, with ISO-flange plate
<b>Rutulinio vožtuvo tarpiklis</b>	PTFE/FKM



## Nuoroda

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)

Daugiau duomenų pagal užklausimą.

## Aprašas

3-way cock, L-bore, full bore

## Papildoma informacija

Other T-positions on request

## Prekė

Pavadinimas	DN	Sriegis	Padėtis	PN (bar)	A (mm)	B (mm)	D (mm)	L (mm)	SW (mm)
K- 07 30 02 84	15	Rp 1/2	L	40	116,0	133,0	20,0	64,5	25
K- 07 30 02 85	20	Rp 3/4	L	40	116,0	137,0	24,0	76,0	31
K- 07 30 02 86	25	Rp 1	L	40	116,0	141,5	30,0	97,0	41
K- 07 30 02 87	32	Rp 1 1/4	L	40	133,0	165,5	37,0	118,0	55
K- 07 30 02 88	40	Rp 1 1/2	L	25	137,0	181,5	43,0	135,0	55
K- 07 30 02 89	50	Rp 2	L	25	161,0	204,0	56,0	157,0	67