


K-XVMK 6

Male connectors, conical male thread acc. to ISO 7-1

HANSA FLEX

Savybės

| | |
|-------------------|----------------------|
| Slėgio diapazonas | Max. 60 bar |
| Temperatūra | Max. 150 °C |
| Medžiaga | Žalvaris, nikeluotas |



Nuoroda

Daugiau duomenų pagal užklausimą.

Prekė

| Pavadinimas | Vamzdžio išorinis Ø | Sriegis | L1 (mm) | SW (rakto dydis) | SW1 (mm) |
|----------------|---------------------|---------|------------|------------------|-------------|
| K- 07 40 20 02 | 4 mm | R 1/8 | 27,0 | 10 mm | 10 |
| K- 07 40 20 03 | 6 mm | R 1/8 | 28,0 | 12 mm | 12 |
| K- 07 40 20 04 | 8 mm | R 1/8 | 29,5 | 12 mm | 14 |
| K- 07 40 20 05 | 6 mm | R 1/4 | 32,5 | 14 mm | 12 |
| K- 07 40 20 06 | 8 mm | R 1/4 | 33,0 | 14 mm | 14 |
| K- 07 40 20 07 | 10 mm | R 1/4 | 37,5 | 17 mm | 19 |
| K- 07 40 20 08 | 8 mm | R 3/8 | 33,0 | 17 mm | 14 |
| K- 07 40 20 09 | 10 mm | R 3/8 | 38,0 | 17 mm | 19 |
| K- 07 40 20 13 | 12 mm | R 3/8 | 39,0 | 19 mm | 22 |
| K- 07 40 20 18 | 10 mm | R 1/2 | 40,5 | 22 mm | 19 |
| K- 07 40 20 19 | 12 mm | R 1/2 | 41,0 | 22 mm | 22 |
| K- 07 40 20 28 | 18 mm | R 1/2 | 43,0 | 26 mm | 32 |