

K-TR AG OR MS NI

Male hose fittings, parallel, with O-ring - nickel-plated brass



HANSA FLEX

Savybės

Darbinė temperatūra Max. 80 °C (with O-ring, NBR)

Slėgis Max. 60 bar

Medžiaga Žalvaris, nikeluotas



Nuoroda

The dimensions of the standard screw fittings may change slightly during the life of the catalogue as a result of optimisation processes.

Daugiau duomenų pagal užklausimą.

Aprašas

Suitable for air, water, oil, steam, etc.

Papildoma informacija

Further types and dimensions on request.

Prekė

| Pavadinimas | Sriegis | žarnai | L1 (mm) | L2 (mm) | SW (rakto dydis) |
|----------------|---------|----------|------------|------------|------------------|
| K- 07 40 13 59 | G 1/8 | LW 6 mm | 30,0 | 6,5 | 14 mm |
| K- 07 40 13 60 | G 1/8 | LW 8 mm | 31,0 | 6,0 | 15 mm |
| K- 07 40 13 61 | G 1/8 | LW 9 mm | 31,0 | 6,0 | 15 mm |
| K- 07 40 13 62 | G 1/4 | LW 6 mm | 32,0 | 8,0 | 17 mm |
| K- 07 40 13 63 | G 1/4 | LW 9 mm | 33,0 | 8,0 | 18 mm |
| K- 07 40 13 64 | G 1/4 | LW 12 mm | 33,0 | 8,0 | 18 mm |
| K- 07 40 49 89 | G 1/4 | LW 8 mm | 32,0 | 8,0 | 17 mm |
| K- 07 40 49 90 | G 1/4 | LW 10 mm | 33,0 | 8,0 | 17 mm |
| K- 07 40 49 96 | G 1/4 | LW 13 mm | 33,0 | 8,0 | 18 mm |
| K- 07 40 49 97 | G 3/8 | LW 6 mm | 33,0 | 9,0 | 20 mm |
| K- 07 40 49 98 | G 3/8 | LW 8 mm | 33,0 | 9,0 | 20 mm |
| K- 07 40 13 65 | G 3/8 | LW 9 mm | 34,0 | 9,0 | 21 mm |
| K- 07 40 49 91 | G 3/8 | LW 10 mm | 34,0 | 9,0 | 20 mm |
| K- 07 40 13 66 | G 3/8 | LW 12 mm | 34,0 | 9,0 | 21 mm |
| K- 07 40 49 92 | G 3/8 | LW 13 mm | 34,0 | 9,0 | 21 mm |
| K- 07 40 13 67 | G 1/2 | LW 12 mm | 36,0 | 11,0 | 26 mm |
| K- 07 40 49 93 | G 1/2 | LW 13 mm | 36,0 | 10,0 | 24 mm |
| K- 07 40 49 94 | G 1/2 | LW 16 mm | 40,0 | 10,0 | 25 mm |
| K- 07 40 49 95 | G 1/2 | LW 19 mm | 40,0 | 10,0 | 24 mm |