
## K-PROP VENTIL LU GA 24 V DC

Proportional valves for controlling the flow of air / gas, 24 VDC, closed when de-energised



Savybės	
Temperatūros diapazonas	Max. 50 °C (G 1/8), Max. 90 °C (G 1/4, G 3/8)
Medžiagos	Air, neutral gases, water, oil
Slėgio diapazonas	Vacuum (max. 8 bar)
Valdymas	Via plug amplifier 0 to 10 V, 0 to 20 mA, 4 to 20 mA
"Failsafe" veikimas	Tight closure in case of loss of voltage
Korpusas, vožtuvo lizdas	Brass
Vidinės dalys	Stainless steel
Vožtuvo lėkštė	FKM
Sandarinimo medžiaga	FKM





## Nuoroda

Daugiau duomenų pagal užklausimą.

## **Aprašas**

## Papildoma informacija

We recommend combining these proportional valves with a plug amplifier, type K-07250999 or K-07251000 We recommend combining these proportional valves with a plug amplifier, type K-07250999 or K-07251000

Pavadinimas	Jungtis	DN	maks. eksploatacinio slėgio diferencialas (bar)	A (mm)	В	C (mm)
K- 07 25 09 91	G 1/4	2	8	85,0	40,0 mm	95,0
K- 07 25 09 92	G 1/4	3	4	85,0	40,0 mm	95,0
K- 07 25 09 93	G 3/8	6	1	85,0	48,0 mm	97,0
K- 07 25 09 94	G 3/8	7	1	85,0	48,0 mm	97,0

www.hansa-flex.com