

K-WV 3/2 MANU DRUCKKNOPF

3/2-way pilot valve, manually operated, with pushbutton, NC

HANSA FLEX

Savybės

| | |
|-------------------------|---|
| Darbinis slėgis | 2.5 - 10 bar (monostable)\n1.0 - 10 bar (bistable)\nMax. vacuum 10 bar (external pilot air) |
| Temperatūros diapazonas | -10 °C to +60 °C |
| 6 bar ir 10 bar srautas | 550 NI/min |
| 6 bar ir 5 bar srautas | 400 NI/min |
| Aktyvinimo įtaisas | Monostable |
| Vožtuvo korpusas | Aliuminis |
| Spyruoklė | Special steel |
| Stūmoklis | Aluminium |
| Sandarinio medžiaga | NBR |



Nuoroda

3 valve positions only in conjunction with a second 3/2-way valve.
Corresponds to a 5/3-way valve.
Daugiau duomenų pagal užklausimą.

Papildoma informacija

Important: The scope of supply does not include a connector. Please order separately.

Prekė

| Pavadinimas | Jungtis | Simbolis | Aktyvinimo įtaisas | Poveržlė |
|----------------|---------|----------|--------------------|-----------|
| K- 07 15 00 76 | G 1/8 | 4 | monostable | Red/black |