

# K-WV 3/2 MANU L DREHHEBEL

3/2-way pilot valves, manually operated, with long wing lever, NC

**HANSA FLEX**

## Savybės

<b>Darbinis slėgis</b>	2.5 - 10 bar (monostable)\n1.0 - 10 bar (bistable)\nMax. vacuum 10 bar (external pilot air)
<b>Temperatūros diapazonas</b>	-10 °C to +60 °C
<b>6 bar ir 10 bar srautas</b>	550 NI/min
<b>6 bar ir 5 bar srautas</b>	400 NI/min
<b>Vožtuvo korpusas</b>	Aliuminis
<b>Spyruoklė</b>	Special steel
<b>Stūmoklis</b>	Aluminium
<b>Sandarinimo medžiaga</b>	NBR



## Nuoroda

3 valve positions only in conjunction with a second 3/2-way valve. <br>Corresponds to a 5/3-way valve.  
Daugiau duomenų pagal užklausimą.

## Papildoma informacija

Important: The scope of supply does not include a connector. Please order separately.

## Prekė

Pavadinimas	Jungtis	Simbolis	Aktyvinimo įtaisas	Jungimo padėtys
<b>K- 07 15 00 82</b>	G 1/8	9	monostable	2
<b>K- 07 15 00 83</b>	G 1/8	10	bistabilus	2
<b>K- 07 15 00 84</b>	G 1/8	11	monostable	3*
<b>K- 07 15 00 85</b>	G 1/8	12	bistabilus	3*